

Charging Post Smart Series -CCL-PM-MIX4-URBAN



Type	<b>CCL-PM-MIX4-Urban</b>
Code	Check availability
Number of sockets	4
<b>Input</b>	
AC power supply	1 P + N + PE
AC Voltage	230V AC +/- 10%
Nominal input current *	64 A
Nominal input power	15 kW
Required power supply capacity	15 kVA
Frequency	50 / 60 Hz
<b>Output</b>	
Maximum output power	7,3 kW (Socket A1)
	3,6 kW (Socket A2)
	7,3 kW (Socket B1)
	3,6 kW (Socket B2)
Maximum output current*	32 A (Socket A1)
	16 A (Socket A2)
	32 A (Socket B1)
	16 A (Socket B2)
AC output voltage	230 V AC 1P + N + PE
<b>Charge system</b>	
Socket A1	Type 2 (UNE EN 62196-2) lock system Mode 3 (IEC 61851)
Socket A2	CEE 7/4 (Schuko) or BS1363 (UK) Mode 1 & Mode 2
Socket B1	Type 2 (UNE EN 62196-2) lock system Mode 3 (IEC 61851)
Socket B2	CEE 7/4 (Schuko) or BS1363 (UK) Mode 1 & Mode 2
<b>Electrical protections</b>	
Overcurrent protections	MCB
Safety protection	RCD 30mA autorecovery (class A)
<b>Energy meter</b>	
Accuracy class in active energy	Class B - EN50470-3
Accuracy class in reactive energy	Class 2 - EN62053-23
Meter standards	EN62052-11, EN62053-21, EN62053-23, EN61010-1
<b>Network connection</b>	
Ethernet	10/100BaseTX (TCP-IP)
<b>General</b>	
Enclosure rating	IP 54 / IK 10
Enclosure material	Stainless steel
Operating temperature	-30 to + 45 °C
Operating humidity	To 95% RH Non-condensing
RFID system	ISO / IEC14443A / B
Display	LCD Backlight double line text
Rear Light beacon	Three color led status
Power limit control	Mode 3 PWM control according ISO/IEC 61851-1
Interface protocol	OCCP / XML
Net weight	65 Kg
<b>Optional devices</b>	
Wireless Communication	3G / GPRS
RCD Protection	RCD class B
Overvoltage protection	*Transient surge protector Type 2 (EN 61643-11)*
* Adjustable power limit control	