

Multipoint Sockets - CCL-WB-SL Single phase



Type	CCL-WB-SL	CCL-WBM SL	CCL-WBC 16 SL	CCL-WBC 32 SL	CCL-WB-SL-MIX
Code	490091	490092	490057	490125	490094
Number of plugs	1	1	1	1	2
Outputs					
Rated output current	16A	32A	16A	32A	32A (Socket A) 16A (Socket B)
Rated output	3,6kW	7,2kW	3.6kW	7.2kW	7.2kW (Socket A) 3.6kW (Socket B)
Output AC voltage	230V AC 1P+N+PE	230V AC 1P+N+PE	230V AC 1P+N+PE	230V AC 1P+N+PE	230V AC 1P+N+PE
Inputs					
Input voltage	230V AC 1P+N	230V AC 1P+N	230V AC 1P+N	230V AC 1P+N	2 x 230V AC 1P+N
Nominal input current	16A	32A	16A	32A	32A 16A
Nominal input power	3,6kW	7,2kW	3.6kW	7,2kW	25kW
Input frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Charge system					
Socket A	Mode 1 & Mode 2	Mode 3 (IEC 61851)	Mode 3 (IEC 61851)	Mode 3 (IEC 61851)	Mode 3 (IEC 61851)
Socket B	-	-	-	-	Mode 1 & Mode 2
Sockets					
Socket A	CEE 7/4 (Schuko) or BS1363 (UK)	Type 2 (UNE EN 62196-2)	Type 1 (UNE EN 62196-2)	Type 1 (UNE EN 62196-2)	Type 2 (UNE EN 62196-2) lock system
Socket B	-	-	-	-	CEE 7/4 (Schuko) or BS1363 (UK)
Energy Meter					
Internal meter					
Cable					
Cable length	-	-	5 meters	5 meters	-
Cable support	-	-	Metal cable support	Metal cable support	-
Network connection					
RS485 (scalable)	Modbus				
General					
Energy Meter	Internal meter				
Enclosure Rating	IP54 /IK10				
Enclosure Material	ABS				
Operating Temperature	-10 to +45C°				
Operating Humidity	To 95% RH Non-condensing				
Net Weight	4kg				
Light beacon	Three color led Status				
Power limit control	Mode 3 PWM control according ISO/IEC 61851-1				
Optional devices					
Extended range temperature	Heater (-30 to +50C°)				
RFID reader System	ISO/IEC 14443A/B				
Connector Lock System	-	Type 2 connector hook	-	-	Type 2 connector hook