

Smart Wallbox Series - CCL-WBC32 SMART



Type	CCL-WBC32 SMART
Code	490124
Number of sockets	1
Input	
AC power supply	1 P + N + PE
AC Voltage	230V AC +/- 10%
Nominal input current **	32 A
Nominal input power	7,2 kW
Required power supply capacity	7,2 kVA
Frequency	50 / 60 Hz
Output	
Rated output power	7,2 kW
Rated output current	32 A 230 V AC 1P + N
Charge system	
Socket A	Mode 3 (IEC 61851) Type 1 cable tethered (UNE EN 62196-2)
Socket B	-
Energy meter	
Accuracy class in active energy	Class B - EN50470-3
Accuracy class in reactive energy	Class 2 - EN62053-23
Meter standards	EN62052-11, EN62053-21, EN62053-23, EN61010-1
Network connection	
Ethernet	10/100BaseTX (TCP-IP)
General	
Cable length	5 meters
Enclosure rating	IP 54 / IK 10
Enclosure material	ABS plastic
Installation mode	Simple installation, 4-point wallfixing
Power limit control	Mode 3 PWM control according ISO/IEC 61851-1
Operating temperature	-10 to +45 °C
Operating humidity	To 95% RH Non-condensing
RFID system	ISO / IEC 14443A / B
Display	LCD Backlight double line text
Rear Light beacon	Three color led status
Interface protocol	OCCP / XML
Net weight	4 Kg
Optional devices	
Wireless Communication	3G / GPRS
Extended Temperature range	-30 to +45 °C (Heater system included)
* Adjustable power limit control	
**power limit control by software	